

values, storing the difference and passing the sum. This process is repeated recursively, pairing up the sums to provide the next scale: finally resulting in $2n - 1$ difference and gives one final sum.

In the future, research will be directed to the forming of reference image which will provide more information for this algorithm in the training process and add the filtering process.

References

- 1) P.J. Phillips, H. Wechsler, J. Huang, and P.J. Rauss, "The FERET Database and Evaluation Procedure for Face Recognition Algorithms," *Image and Vision Computing J.*, vol. 16, no. 5, pp. 295-306, 1998
- 2) D. Kumar, C.S Rai, and S. Kumar, "Face Recognition using self-organizing Map and Principal Component Analysis" in *Proc. On Neural Networks and Brain, ICNNB 2005*, Vol 3, Oct 2005.
- 3) Paul viola and Michael J. Jones. "Robust real-time object detection", *IEEE conference on computer vision and pattern Recognition*, 2001.
- 4) Y. Freund and R. E schapire "A decision theoretic generalization of on-line learning and an application to boosting" *J. Comput. Syst. Sci.*, Vol 55, no. 1, pp. 119-139, 1997.
- 5) R. E. Schapire, "The boosting approach to machine learning: An overview", *Proc. MSRI Workshop Nonlinear Estimation and Classification 2002*
- 6) "Discrete Wavelet Transforms: Theory and Implementation" Tim Edwards Stanford University, September, 1999
- 7) R. E. Schapire, "The boosting approach to machine learning: An overview" in *Proc. MSRI Workshop Nonlinear Estimation and Classification 2002*, pp. 149-172.1.
- 8) Kinh Tieu and Paul Viola, *Boosting Image Retrieval*. In *proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, 2000.